PEB Services B.V. Stephensonstraat 30, PO Box 186 2700 AD Zoetermeer, The Netherlands Telephone 31-(0)79-3417 714 Telefax 31-(0)79-3313 502



Services@peb.nl

Signature:

HOTTAP SPECIFICATIO	ON SHEET	
Customer:		Date of operation:
Customer ref.:		Contact person:
Contact person:		During operation:
Telephone nr.:		Telephone nr.:
Handled by:		Location of operation:
Date:		P.E.B. ref.:
HOTTAP SPECIFICATION	ONS	PARTICULARS OF AVAILABLE EQUIPMENT
Hottap nom. size:		Outside diameter:
Hottap act. size:		Wall thickness:
Quantity:		Internal diameter:
Product:		Mat. specification:
Aggressive?		Type of valve:
Pressure/Temp.:	kg/cm²Cº	Flange connection:
rressure, remp	Kg/cmC-	Trainge connection.
Hottap on a:	pipeline/tankwall	Coating (other than paint)
	blindflang	Location: intern. extern.
	valve gate	Thickness:
Position of the machin	ne: horizontal vertical	Specification:
HOTTAP SPECIFICATION	<u>ons</u>	
A=height stub	mm	⊥ øD
B=face to face valve	mm	
C=total height	mm	
D=intern. diam. Valve	mm	
E=distance flange/gate	e mm	
F=restriction of gate	mm	
G=internal diam. stub	mm	
H=available space	mm	
K=height from ground	level mm	d ⊗C
0 0		*
Scaffolding present	☐ no ☐ yes	
Crane present	no yes minkg	
Compressed air	no yes min. 3m/min. 6 ba	ur .
Gaskets and bolting	PEB klant	
Guskets und boiting	- None	
Remarks		
FOR ACCEPTANCE OF	<u>OPERATION</u>	
Coupon submitted:	yes no	Order:
Waiting time:		Reason waiting time:
		Name customer:

Signature: