PEB Services B.V. Stephensonstraat 30, PO Box 186 2700 AD Zoetermeer, The Netherlands Telephone 31-(0)79-3417 714 Telefax 31-(0)79-3313 502

LINESTOP DATA SHEET



Telefax 31-(0)79-3313 502	
Services@peb.nl	İ

ſ	Lino Dotaile	Unetroam	Downstroam	Plugging Dotails
				Fax / E-mail:
Site Address:				Tel:
	Customer:			Site Contact:

Line Details Upstream Downstream		Plugging Details		
Line Size [inch/mm]			Purpose of Isolation	
Line Wall Thickness [mm]			Type of Operation [Single / Two Position]	
Line Material [CS / LTCS / SS / DUPLEX / DI / HPE]			Bypass Required [Y/N]	
Line Construction [Seamless/Seamed/Spiral Wound]			Bypass Size [inch/mm]	
Lining/Coating Type & Thickness			Bypass Type [Temporary/Permanent]	
Line Contents [specify line medium]			Distance between Isolations [m]	
Actual Operating Pressure during Operation [Barg]			Baghole Size - Hydrocarbons only [mm]	
Actual Operating Temperature during Operation [°C]			Vent/Purge/Drain Size [inch/mm]	
Flow Velocity [m/sec]			Orientation of Linestop Equipment	
Is the line piggable [Y/N]			Clearance Available	
Orientation of Line [Horizontal / Vertical / Inclined]			Length of Pipe Available	
			Duration of Isolation [hours/days]	

